

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/001S/1500 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.4% w/w max |
| 3 | Fe | : | 1500 ppm max |
| 4 | Na ₂ CO ₃ | : | 5% w/w max |
| 5 | Appearance | : | Red Flakes |

Application : This chemical is used in Leather Industry

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/002S/150 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.2% w/w max |
| 3 | Fe | : | 150 ppm max |
| 4 | Na ₂ CO ₃ | : | 2% w/w max |
| 5 | Appearance | : | Yellow Flakes |

Application : This chemical is used in Leather Industry

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/003S/80 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.2% w/w max |
| 3 | Fe | : | 80 ppm max |
| 4 | Na ₂ CO ₃ | : | 2% w/w max |
| 5 | Appearance | : | Yellow Flakes |

Application : This chemical is used in Leather Industry

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/004S/50 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.2% w/w max |
| 3 | Fe | : | 50 ppm max |
| 4 | Na ₂ CO ₃ | : | 2% w/w max |
| 5 | Appearance | : | Yellow Flakes |

Application : This chemical is used in Leather Industry

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/005S/30 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.05% w/w max |
| 3 | Fe | : | 30 ppm max |
| 4 | Na ₂ CO ₃ | : | 2% w/w max |
| 5 | Appearance | : | Yellow Flakes |

Application : This chemical is used in Leather Industry

| | | |
|----------------------|---|-------------------------------|
| SPECIFICATION NUMBER | : | SPEC/CHD/006S/20 |
| TITLE | : | SODIUM SULPHIDE FLAKES 60%MIN |

| SR NO | PARAMETERS | | SPECIFICATION |
|-------|---------------------------------|---|---------------|
| 1 | Na ₂ S | : | 60% w/w min |
| 2 | Water Insoluble | : | 0.03% w/w max |
| 3 | Fe | : | 20 ppm max |
| 4 | Na ₂ CO ₃ | : | 2% w/w max |
| 5 | Appearance | : | Yellow Flakes |

Application : This chemical is used in Leather Industry
